



Koolkut® 8052B

Phillips 66® Koolkut 8052B is a light-colored, low viscosity, chlorine-free tri-purpose oil formulated for use as a high-performance cutting oil, gear oil and hydraulic fluid in metalworking machines.

Koolkut 8052B is formulated with fatty acids, polymers and a chlorine-free extreme-pressure additive package. The combination of extreme-pressure properties and good oiliness characteristics helps minimize cutting tool wear and ensure a good surface finish on the machined parts.

Koolkut 8052B is transparent, allowing good observation of the machining operation. It is non-corrosive to copper and copper alloys and provides good rust protection for ferrous metals. The absence of chlorine ensures greater handling safety and safe disposal of waste oil.

Koolkut 8052B is ideal for use in automatic screw machines that use one fluid to lubricate the cutting tool and workpiece, the machine gears, and the hydraulic pumps and motors. It also is suitable for use in lathes where mixing of the hydraulic fluid and cutting oil may occur. The performance capabilities of most cutting oils are greatly reduced when diluted with typical hydraulic oils. Using Koolkut 8052B as a lubricating oil and cutting oil avoids this problem.

Applications

Koolkut 8052B is recommended for light to heavy-duty machining of ferrous and non-ferrous metals. Typical applications include:

- Boring
- Broaching
- Drilling
- Gear hobbing
- Grinding
- Milling
- Planing
- Sawing
- Screw machining
- Shaping
- Tapping

Koolkut 8052B is suitable for machining a wide variety of metals ranging from steels with a machinability rating of 90%, to metals such as inconel, monel and titanium with machinability ratings below 50%.

Features/Benefits

- Tri-purpose cutting oil, gear oil and hydraulic oil
- Helps extend cutting tool life
- Good surface finish
- Good rust protection
- Non-corrosive to copper and copper alloys
- Chlorine-free for reduced environmental impact
- Transparent for good visibility of the machining operation

**Tri-Purpose
Cutting Oil,
Gear Oil &
Hydraulic Oil**

**KEEPING THE
WORLD
RUNNING
SMOOTHLY.**





Koolkut® 8052B

Typical Properties	
ISO Grade	22
Specific Gravity @ 60°F	0.901
Density, lbs/gal @ 60°F	7.50
Color, ASTM D1500	3.0
Flash Point (COC), °C (°F)	177 (350)
Pour Point, °C (°F)	-34 (-30)
Viscosity	
cSt @ 40°C	22.0
cSt @ 100°C	3.9
SUS @ 100°F	116
SUS @ 210°F	39.4
Viscosity Index	40
Acid Number, ASTM D974, mg KOH/g	3.5
Copper Corrosion, ASTM D130	1b
Chlorine, wt %	Nil
Fatty Oil, wt %	8.0
Phosphorus, wt %	0.10
Sulfur, wt %	0.30

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

