



SHELL PELLA[®] OIL A

Versatile, low viscosity machining oil

Product Description

Shell Pella[®] Oil A is mild-odor, light colored, low viscosity machining oil. It does not contain any additives, and is sometimes referred to as “mineral seal” oil.

Applications

- grinding glass lenses
- cutting stone and ceramics with diamond-tipped saws
- light machining applications

Features/Benefits

- low viscosities
- additive free
- multiurpose

Typical Properties of Shell Pella[®] Oil A

	Test Method	
Product Code		61900
Gravity, °API	D 1298	41.2
Viscosity: @ 40°C, cSt	D 445	4.3
Flash Point, COC, °F	D 92	285
Flash Point, PMCC, °F	D 93	255
Pour Point, °F	D 97	30
Aniline Point, °F	D 611	188
Copper Corrosion @ 212°F	D 130	1b
Sulfur, wt%	D 2622	0.09

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet at <http://www.shell-lubricants.com/msds/>. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please call **1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>.

