BIZOL Allround 5W-30 C2/C3

BIZOL

Martin-Buber-Straße 12, 14163 Berlin, Germany

Benefits

- 1. reduces particle build-up in diesel particulate filters
- 2. reduce deposits and sludge build-up
- 3. covers both C2 and C3 ACEA requirements

Product Description

BIZOL Allround 5W-30 C2 / C3 has been expertly engineered to help prolong the life and maintain the efficiency of the emission systems in both diesel and gasoline engines. It has been developed to help deliver outstanding performance and protection in conjunction with improved fuel economy. BIZOL Allround 5W-30 C2 / C3 contains premium mid-SAPS additive technology for ACEA C2/C3 requirements. Not suitable for VW R5 and V10 engines manufactured before 2007.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

ACEA C2/C3

VW 504 00/507 00 | MB 229.51 | BMW LL 04 | Porsche C30

Available Packages

1 L Art. 86610

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	
Viscosity at 40 °C	73,0 mm²/s	ASTM D 7042
Viscosity at 100 °C	10,9 mm²/s	ASTM D 7042
Viscosity index	> 160	ASTM D 2270
Density at 15 °C	850 kg/m³	DIN EN ISO 12 185
Pour Point	<-30 °C	ISO 3016

BIZOL Allround 5W-30 C2/C3



Martin-Buber-Straße 12, 14163 Berlin, Germany

Technical Data

Name	Value	Method
Flash Point (Cleveland)	210 °C	ISO 2592
Total base number (TBN)	> 6 mg KOH/g	ASTM D 2896

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.