

Benefits

1. optimum fuel savings
2. excellent anti-wear and corrosion properties
3. effective for gasoline engines with catalytic converters and with turbochargers

Product Description

BIZOL Protect 5W-30 is a high performance, fuel economy gasoline engine oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives. It is especially formulated for the lubrication of modern gasoline engines of passenger vehicles, vans and SUVs. The effective formulation of **BIZOL Protect 5W-30** provides a superior lubrication for all major engine components resulting in a longer engine life. It provides improved protection for the latest emission control systems by meeting the specifications ILSAC GF-5 and GM Dexos 1 Gen. 2.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

API SN | ILSAC GF 5 | GM DEXOS 1 Gen. 2
Ford WSS-M2C-946-A | Chrysler MS-6395 | GM 6094 M | Toyota | Honda |
Nissan | Mazda | Hyundai

Available Packages

1 L Art. 81320 4 L Art. 81326 200 L Art. 81324

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	
Viscosity at 40 °C	62,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	10,2 mm ² /s	ASTM D 7042
Viscosity index	> 160	ASTM D 2270

Technical Data

Name	Value	Method
Density at 15 °C	855 kg/m ³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Flash Point (Cleveland)	>220 °C	ISO 2592
Total base number (TBN)	7,7 mg KOH/g	ASTM D 2896

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.