



Performance Bio NC Lite

High performance neat cutting oil

Description

Castrol Performance Bio NC Lite is a chlorine free, multi-metal compatible, high performance neat cutting oil, which is based on plant oil and synthetic hydrocarbon technology. Customer feedback* has highlighted low misting characteristics, robust oxidation stability and excellent cooling properties, which can help create productivity increases.

Application

Performance Bio NC Lite is designed for gear manufacturing and general cutting operation of ferrous and nonferrous metals.

.. suggested core application .. possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed steel / nickel-chromium alloys	Titanium alloys	Aluminium alloys	Yellow metals
Honing/ Superfinishing
Grinding
Drilling
Broaching
Gear manufacturing
General machining

Advantages

- Customers have commented* favorably on the low misting and smoking characteristics. This helps to reduce oil consumption.
- High oxidation stability increases product lifetime and reduce oil consumption
- Plant oil based technology shows better cooling properties than traditional mineral oils. This characteristic could help support productivity increases
- Our chlorine free formulation can help reduce disposal costs
- Low odour and light colour help to improve the working environment
- Multi-metal compatibility provides opportunity for product consolidation

* Based on feedback received from our customers in the USA using Performance Bio NC fluids

Typical Characteristics

Properties	Standard	Unit	Data
Appearance	Visual		Light Yellow
Viscosity @ 40°C	DIN 51562 ASTM D 445	mm ² /s	25
Viscosity @ 100°F	ASTM D 445	SUS	137
Flashpoint COC	ISO 2592 ASTM D 92	°C/°F	215/420
Copper corrosion	ISO 2160 ASTM D 130	3 hr at 100 °C	1b

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress. Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always. For more details, please refer the product safety data sheet.

Performance Bio NC Lite
17 Oct 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial

