



Castrol Vecton Long Drain 10W-30 CK-4

Part Synthetic Diesel Engine Oil

Description

NEW CASTROL® VECTON® LONG DRAIN 10W-30 CK-4 with unique System Pro Technology™ is an advanced part-synthetic heavy duty engine oil. Conforming to the requirements of PC-11 engine oil technology, it can be used in diesel engines where API CK-4, CJ-4, and previous diesel engine oil categories are required. It is specifically engineered to deliver longer oil life, enabling longer service intervals even under severe operating conditions.

ADVANTAGES:

Castrol VECTON LONG DRAIN 10W-30 CK-4 delivers extended drain intervals of **up to 80,000 miles or 1,000hrs***

New technology developments in diesel engines have led to lower emissions in heavy duty vehicles. These technology advances result in increasing levels of torque within the engine, leading to higher pressures and temperatures. Castrol VECTON Long Drain 10W-30 CK-4 with unique System Pro Technology™ adapts to increased pressure and temperature with its proven shear stability and oxidation performance, extending the useful life of the oil for longer service intervals and higher productivity.

(*in combination with and following a proper used oil analysis program.)

USER BENEFITS INCLUDE:

- Excels under high pressure: engine combustion pressures are increasing, which puts increased pressure on key engine parts. Castrol VECTON Long Drain 10W-30 CK-4 with unique System Pro Technology™ is formulated to hold its viscosity under high shear contacts to extend oil life.
- When it comes to neutralizing the harmful acids and combustion by-products that cause corrosion in bearings, Castrol VECTON Long Drain 10W-30 CK-4 maintains outstanding TBN level even while operating at maximum drain intervals.
- Performs at high temperature: engine oil is subjected to areas of very high temperature in modern engines, causing oxidation and oil thickening. Castrol VECTON Long Drain 10W-30 CK-4 is formulated to fight oxidation while extending oil life.

Typical Characteristics

Name	Method	Units	Vecton Long Drain 10W-30 CK-4
Density @ 15C	ASTM D4052	g/ml	0.87
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	12.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	82
Viscosity Index	ASTM D2270	None	144
Ash, Sulphated	ASTM D874	% wt	1.0
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.7
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	205
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6100

Product Performance Claims

API CK-4
JASO DH-2
CAT ECF-3
Cummins CES 20086
DDC DFS 93K222
Deutz DQC III-10LA
Meets Ford WSS-M2C171-F1
Mack EOS-4.5
MB-Approval 228.31
RVI RLD-3
Volvo VDS-4.5

Vecton Long Drain 10W-30 CK-4
15 Jul 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Wakefield Canada, Limited, 3620 Lakeshore Blvd West, Toronto, Ontario, Canada - M8W 1P2

Plant Office:3660 Lakeshore Blvd West , Toronto, ON M8W 1P2 -
Phone 1-800-268-5339 Fax 416-252-7315 Plant Office telephone: 1 800 268-5339 Trade: 1 888 CASTROL Consumer: 1 800 CASTROL Technical Inquiries: 1 800 462-0835

E-mail info@wakefieldcanada.ca Website www.wakefieldcanada.ca www.castrol.com

Page: 2/2