



# CHEVRON SHINGLE OIL

## PRODUCT DESCRIPTION

Chevron Shingle Oil is designed for use on shake roofs, log homes, wood siding, and fences.

## CUSTOMER BENEFITS

Chevron Shingle Oil delivers value through:

- **Improved appearance** — Helps maintain the structural strength and stability of the wood by reducing cupping, cracking, and splitting caused by cyclical exposure to sun and rain.
- **Prolonged useful life** — Helps prolong wood's useful life by reducing the effects of weathering.
- **Ability to retard aging** — Helps absorb into the wood and improves the appearance of shake roofs, log homes, wood siding, and fencing.

## FEATURES

Chevron Shingle Oil is a straw colored, low viscosity oil designed for use as a shingle or shake dressing for shake roofs, wooden fencing, wood siding, and log homes.

Chevron Shingle Oil penetrates the wood surface to enhance or replace natural oils and resins leached out by cyclical exposure to sun and rain.

Although Chevron Shingle Oil retards the aging process, it will not renew wood that is already weather damaged.

## APPLICATIONS

Loose dirt and debris should be removed before the oil is applied. The roof should be hosed with water 24 hours prior to application to lessen the possibility of over application. Alternatively, a licensed contractor can power wash the roof thereby removing weather-damaged wood, allowing oil to absorb into new wood.

Chevron Shingle Oil may be applied by brushing or spraying. The typical application rate is 150-300 square feet per gallon. Application rate depends on the

type of wood and the rate at which the oil saturates the wood.

Do not overapply — Over application may lead to shingle or shake "cupping" and the presence of oil in rainwater runoff.

Do not add color pigments — as they will lump and settle out.

Do not walk on treated surfaces — Chevron Shingle Oil is a petroleum oil and is slippery.

Do not use on flat surfaces, such as decks.

Properly licensed contractors may add certain chemicals, such as antifungal agents and other substances, to Chevron Shingle Oil. Be sure to find out what safety or health restrictions may apply to these additives.

To prevent possible damage to foliage:

- Avoid spraying in windy conditions
- Avoid spraying directly on plants

## TYPICAL TEST DATA

Product Number	213304
SDS Number	4223
API Gravity	23.4
Viscosity, Kinematic cSt at 40°C	21.7
cSt at 100°C	3.5
Volatile Organic Compound, g/L	130
Flash Point, COC, °C(°F)	183(361)
Pour Point, °C(°F)	-38(-36)
Color, ASTM	0.5

Minor variations in product typical test data are to be expected in normal manufacturing.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

6 January 2014  
IO-210

© 2007-2014 Chevron U.S.A. Inc. All rights reserved.

Chevron and the Chevron Hallmark are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

