



MEROPA®

68, 100, 150, 220, 320, 460, 680, 1000, 1500

PRODUCT DESCRIPTION

Meropa® gear lubricants are premium quality extreme pressure gear oils with excellent load carrying capacity, water demulsibility, oxidation stability, and corrosion protection.

CUSTOMER BENEFITS

Meropa gear lubricants deliver value through:

- **Gear set efficiencies** — High thermal stability EP system helps maintain clean gear and bearing surfaces, minimizing deposits which interfere with effective lubrication. High oxidation stability limits in-service viscosity increases, which can lead to energy losses.
- **Long equipment life** — Effective EP system forms a protective film in areas of metal-to-metal contact, minimizing wear rates and maintaining efficient transfer of power. Good water separation and effective rust inhibitors protect surfaces against rust and corrosion. High thermal stability additive system minimizes the formation of high temperature compounds which can be corrosive to bearing materials. The effective corrosion inhibitor provides additional protection for metal components.
- **Long oil life** — Effective oxidation inhibitors and copper passivator minimize oil oxidation, limiting viscosity increase and promoting long drain intervals.

FEATURES

Meropa gear lubricants are high performance, multipurpose gear lubricants designed for many types of industrial gear lubrication services where loads and shock loadings are high.



APPLICATIONS

Meropa gear lubricants are recommended for:

- industrial enclosed gearing where an AGMA extreme pressure lubricant is specified
- bath, splash, circulating, or spray mist lubrication as applicable to the proper viscosity grade
- general industrial plant lubrication where the performance properties of an AGMA extreme pressure lubricant is required

Meropa gear lubricants meet the requirements of:

- **AGMA** EP 9005-E02 (ISO 68, 100, 150, 220, 320, 460, 680, 1000, 1500)
- **DIN** 51517-3 (CLP)
- **MAG Cincinnati, Cincinnati Machine** P-63 (ISO 68), P-76 (ISO 100), P-77 (ISO 150), P-74 (ISO 220), P-59 (ISO 320), P-35 (ISO 460), P-78 (ISO 1000)
- **U.S. Steel** 224 Specification (ISO 220, 320, 460, 680)

Meropa gear lubricants (ISO 68, 100, 150, 220, 320, 460) are suitable for use in **Bijur** oil application equipment.

Meropa gear lubricants have a typical sulfur-phosphorus odor characteristic of industrial gear oils. A ventilated environment is recommended during use.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 July 2016
GL-37

© 2008-2016 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark and Meropa are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

TYPICAL TEST DATA

ISO Grade	68	100	150	220	320	460	680
Product Number	277209	277219	277210	277211	277212	277213	277214
SDS Number	23551	23551	23551	23551	23551	23551	23551
AGMA Grade	2 EP	3 EP	4 EP	5 EP	6 EP	7 EP	8 EP
API Gravity	31.0	30.6	29.7	28.4	27.3	26.3	26.0
Viscosity, Kinematic cSt at 40°C cSt at 100°C	64.6 8.6	95.0 11.0	142 14.4	209 18.8	304 23.2	437 29.4	646 39.8
Viscosity, Saybolt SUS at 100°F SUS at 210°F	334 55	495 64	744 77	1102 96	1618 116	2341 144	3467 194
Viscosity Index	104	100	100	100	95	95	100
Flash Point, °C(°F)	225(437)	225(437)	240(464)	245(473)	245(473)	245(473)	260(500)
Pour Point, °C(°F)	-33(-27)	-30(-22)	-30(-22)	-21(-5)	-18(0)	-15(+5)	-12(+10)
Timken OK Load, lb	65	65	65	65	65	65	65
FZG Pass Stage, ASTM D5182	12	12	12	12	12	12	>12

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

1 July 2016
GL-37

TYPICAL TEST DATA

ISO Grade	1000	1500
<i>Product Number</i>	277215	277216
<i>SDS Number</i>	23551	23551
AGMA Grade	8A EP	9 EP
API Gravity	25.9	25.7
Viscosity, Kinematic cSt at 40°C cSt at 100°C	950 53.9	1425 74.0
Viscosity, Saybolt SUS at 100°F SUS at 210°F	5115 262	7699 359
Viscosity Index	107	114
Flash Point, °C(°F)	260(500)	260(500)
Pour Point, °C(°F)	-12(+10)	-12(+10)
Timken OK Load, lb	65	65
FZG Pass Stage, ASTM D5182	>12	>12

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

1 July 2016
GL-37

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

1 July 2016
GL-37

