

# PENNZOIL<sup>®</sup> DEX MERC ATF High Performance Automatic Transmission Fluid

## TECHNICAL DATA SHEET



PENNZOIL<sup>®</sup> DEX MERC ATF is a high quality automatic transmission fluid based on high viscosity index mineral oils and carefully selected additives. It is blended to meet the stringent requirements of leading automotive transmission manufacturers for GM DEXRON<sup>®</sup>-III(H) and Ford MERCON<sup>®</sup> historic performance.

### PERFORMANCE, FEATURES & BENEFITS

- **Friction modified**

Provides consistent, reliable, smooth and trouble free operation of automotive transmission systems.

- **High oxidation resistance**

Resistant to oil degradation and keeps automatic transmissions clean.

- **Good shear-stability**

A special 'VI' improver minimises the changes in viscosity with operating temperature.

- **Dependable anti-wear and gear protection**

Long component life

- **Low temperature performance**

Excellent oil fluidity at low temperatures

### MAIN APPLICATIONS

- Passenger car automatic transmissions
- Heavy duty automatic transmissions
- Power steering units
- Certain hydraulic applications calling for oils meeting ISO VG 32-46-68 viscosity requirements

### SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Suitable for use in all vehicles where GM DEXRON<sup>®</sup> III, Ford MERCON<sup>®</sup> or Allison C-4 fluids are required. Do not use where GM Dexron<sup>®</sup> VI or Ford Mercon<sup>®</sup> V/MERCON<sup>®</sup> SP/MERCON<sup>®</sup> LV /Type F fluids are specified.

#### Colour

Pennzoil<sup>®</sup> DEX MERC ATF is dyed red for identification purposes.

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

To find the right Pennzoil<sup>®</sup> product for your vehicles and equipment, please consult [www.pennzoil.com](http://www.pennzoil.com) to look up the right motor oil recommendation using our oil selector.

### TYPICAL PHYSICAL CHARACTERISTICS

Properties			Method	Pennzoil <sup>®</sup> DEX MERC ATF
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	ISO 3104	33.8
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	ISO 3104	7.3
Viscosity Index			ISO 2909	175
Density	@15°C	kg/l	ISO 12185	0.857
Flash Point (COC)		°C	ISO 2592	180
Pour Point		°C	ISO 3016	-48

# **PENNZOIL<sup>®</sup> DEX MERC ATF** *High Performance Automatic Transmission Fluid*

These characteristics are typical of current production. While future production will conform to Pennzoil's<sup>®</sup> specification, variations in these characteristics may occur.

## **HEALTH, SAFETY & ENVIRONMENT**

### **Health and Safety**

Pennzoil<sup>®</sup> DEX MERC ATF is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from [www.epc.shell.com](http://www.epc.shell.com)

### **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## **ADDITIONAL INFORMATION**

### **Advice**

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Help Desk.

DEXRON<sup>®</sup> is a trademark in many countries belonging to General Motors Company.

MERCON<sup>®</sup> is a trademark in many countries belonging to Ford Motor Company.

