



PRODUCT INFORMATION

A product of Southern Counties Lubricants, LLC

Olympus Synthetic Dexos Gen 2, 5W-30 and 0W-20 GF-5 SN-RC

PREMIUM HIGH PERFORMANCE ENGINE OIL – ILSAC GF-5, API SN, SN-RC

Product Description

Olympus Synthetic Dexos Gen 2 is high performance synthetic oil designed to meet the latest car manufacturers warranty requirements. Specifically formulated to meet the demands of the small displacement high RPM fuel efficient engines found in today's domestic and foreign automobiles. These engines experience higher operating temperatures and require motor oil which offers maximum protection against both viscosity and thermal breakdown.

Specific viscosity grades meet all the requirements specified by **API SN, API SN-RC, ILSAC GF-5** and **Dexos Gen 2** specification.

Advantages & Uses

- **Olympus Synthetic Dexos 2** exceeds **API Service Classification SN, API SN-RC, ILSAC GF-5** and **Dexos Gen 2**.
- Recommended for passenger cars, light duty pickups, motorcycle and other gasoline engines in mobile and stationary service, where this specification is specified.

Features

- **Olympus Synthetic Dexos Gen 2** meets and exceeds all U.S. car maker warranty requirements.
- High oxidation stability - protects engine from oil thickening, high temperature sludge and varnish deposits.
- Shear stable viscosity index improver-protects against viscosity breakdown in severe service.
- Superior detergency.
- High TBN / alkaline reserve effectively neutralize corrosive acids, thereby provide longer drain interval.

Test, SAE	ASTM	5W-30	0W-20
Sp. Gravity	D-4052	0.846	0.851
Flash Point, °C	D-93	226	220
Pour Point, °C	D-97	-40	-40
Viscosity @ 100° C cSt	D-445	8.5	11.0
Viscosity @ -30 °C CCS	D-5293	5700	5000
Viscosity Index	D-2270	169	165
Appearance	Visual	Bright & Clear	Bright & Clear
Zinc (Wt. %)	D-4151/ D-5185	0.085	0.085
Phos (Wt. %)	D-4951	0.77	0.077
Sulfur (Wt. %)	D-2622/ D-4951	0.90	0.9
TBN	D-2896	8.7	8.7

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY