# PIRANHA TRI-PURPOSE OIL T-35

TRIPLE PURPOSE LUBRICANT-MACHINE OIL-HYDRAULIC OIL-CUTTING OIL



### A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

#### **Product Description**



**TRI-PURPOSE OIL T-35** is a superior tri-purpose, transparent, non-corrosive, light colored, anti-mist cutting oil fortified with a special chlorine extreme pressure additive and lubricity additive.

The tri-purpose features of this oil allows its use as a cutting oil, hydraulic oil and machine oil in automatic screw machines. This eliminates the intermingling of cutting oil with the machine oils and hydraulic oils as the

The contamination of machine oil and hydraulic oil by active corrosive cutting oils can have serious consequences in automatic screw machines. This can best be avoided by using one oil for all three applications.

result of leakage from one system to another.

## Applications & Uses:

- Used as cutting oil, machine oil and hydraulic oil in automatic screw machines.
- Well suited for machining non-ferrous metals such as brass, bronze, copper, aluminum and magnesium.
- Used in machining steel and its alloys where machining requirements range from light to moderately severe (60-100 machinability).
- Lubricity additive makes product an ideal way lubricant.
- Anti-mist allows use of product in high speed cutting operations.

#### Features & Benefits:

- Triple purpose reduced inventory. Economical.
- Anti-mist/transparent good visibility of work piece.
- Eliminates contamination problem between machine oil and cutting oil.
- Non-corrosive to work or machine parts. Non-staining.
- Good work piece surface finish.
- High lubricity for long tool life.

#### **Typical Test Data**

TEST, ISO GRADE	ASTM	32
Gravity °API	D-4052	29.5
Flash Point, °C.	D-92	202
Fire Point, °C.	D-92	221
Pour Point, °C.	D-97	-12
Viscosity:		
cSt. @ 40 ℃.	D-445	30
cSt.@100 ℃.	D-445	5.3
Viscosity Index	D-2270	103
Color	D-1500	1.0
Chlorine, WT. %	D-1100	2.3

\* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY. VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

## **TECHNICAL PRODUCT INFORMATION**