According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Shell Rotella T5 NG 15W-40

Version Revision Date: SDS Number: Print Date: 09/01/2018 800010025929 2.0 08/31/2018 Date of last issue: 02/09/2016 **SECTION 1. IDENTIFICATION** : Shell Rotella T5 NG 15W-40 Product name Product code : 001F4538 Manufacturer or supplier's details Manufacturer/Supplier : Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA SDS Request : (+1) 877-276-7285 Customer Service 2 **Emergency telephone number** Spill Information : 877-504-9351 Health Information : 877-242-7400 Recommended use of the chemical and restrictions on use Recommended use : Engine oil. **SECTION 2. HAZARDS IDENTIFICATION** GHS classification in accordance with 29 CFR 1910.1200

| Skin sensitisation | : | Category 1 |
|--------------------------|---|---|
| GHS label elements | | |
| Hazard pictograms | : | |
| Signal word | : | Warning |
| Hazard statements | : | PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: H317 May cause an allergic skin reaction. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria. |
| Precautionary statements | : | Prevention: P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version | Revision Date: | SDS Number: | Print Date: 09/01/2018 |
|---------|----------------|--------------|--------------------------------|
| 2.0 | 08/31/2018 | 800010025929 | Date of last issue: 02/09/2016 |

P302 + P352 IF ON SKIN: Wash with plenty of water and soap. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label: Contains calcium sulphonate.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346. * contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9.

Hazardous components

| Chemical name | Synonyms | CAS-No. | Concentration (% w/w) |
|--|--------------------------|--------------|-----------------------|
| Alkylphenol | dodecylphenol | 27193-86-8 | 0.1 - 0.29 |
| Polyolefin amide alkeneamine borate | Borated succin- imide | Not Assigned | 1 - 3 |
| Calcium alkaryl sul- phonate | | Not Assigned | 1 - 3 |
| Polyolefin amide alkeneamine | | Not Assigned | 1 - 3 |
| Interchangeable low viscosity base oil (<20,5 cSt @40°C) * | | Not Assigned | 0 - 90 |

SECTION 4. FIRST-AID MEASURES

| If inhaled | : | No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice. |
|-------------------------|---|--|
| In case of skin contact | : | Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version 2.0 | Revision Date: 08/31/2018 | | DS Number: 0010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 | |
|---|---|---|--|---|--|
| | | | If persistent irritat | ion occurs, obtain medical attention. | |
| In ca | se of eye contact | : | Remove contact I rinsing. | pious quantities of water. enses, if present and easy to do. Continue ion occurs, obtain medical attention. | |
| If swallowed | | : | In general no treatment is necessary unless large quantities are swallowed, however, get medical advice. | | |
| Most important symptoms and effects, both acute and delayed | | : | may include itchir Oil acne/folliculitis of black pustules | (allergic skin reaction) signs and symptoms og and/or a rash. s signs and symptoms may include formation and spots on the skin of exposed areas. sult in nausea, vomiting and/or diarrhoea. | |
| Prote | ection of first-aiders | | | ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings. | |
| med | ation of any immediate ical attention and special ment needed | : | Treat symptomati | cally. | |

SECTION 5. FIRE-FIGHTING MEASURES

| Suitable extinguishing media | : | Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only. |
|---|---|---|
| Unsuitable extinguishing media | : | Do not use water in a jet. |
| Specific hazards during fire- fighting | : | Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. |
| Specific extinguishing meth- ods | : | Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. |
| Special protective equipment for firefighters | : | Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469). |

SECTION 6. ACCIDENTAL RELEASE MEASURES

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Vers 2.0 | sion | Revision Date: 08/31/2018 | | S Number: 0010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|-------------|---------------------------|---|---|---|--|
| | tive equ | al precautions, protec- ipment and emer- procedures | : | Avoid contact with | skin and eyes. |
| | Environmental precautions | | : | nation. Prevent fro | ontainment to avoid environmental contami- om spreading or entering drains, ditches or nd, earth, or other appropriate barriers. |
| | | | | Local authorities s cannot be contained | hould be advised if significant spillages ed. |
| | | s and materials for ment and cleaning up | : | Prevent from spre or other containme Reclaim liquid dire Soak up residue w | t. Avoid accidents, clean up immediately. ading by making a barrier with sand, earth ent material. ectly or in an absorbent. <i>v</i> ith an absorbent such as clay, sand or other and dispose of properly. |
| | Additior | nal advice | : | see Chapter 8 of t | election of personal protective equipment his Safety Data Sheet. isposal of spilled material see Chapter 13 of heet. |

SECTION 7. HANDLING AND STORAGE

| Technical measures | : | Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. |
|---|---|---|
| Advice on safe handling | : | Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires. |
| Avoidance of contact | : | Strong oxidising agents. |
| Product Transfer | : | Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation. |
| Further information on stor- age stability | : | Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. |
| | | Store at ambient temperature. |

Shell Rotella T5 NG 15W-40

| Version 2.0 | Revision Date: 08/31/2018 | SDS Number: 800010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|----------------|------------------------------|-----------------------------|---|
| Packa | aging material | | al: For containers or container linings, use mild nsity polyethylene. prial: PVC. |
| Conta | iner Advice | | ntainers should not be exposed to high tem- use of possible risk of distortion. |

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parame- ters / Permissible concentration | Basis |
|-------------------|--------------|-------------------------------------|--|----------|
| Oil mist, mineral | Not Assigned | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| Oil mist, mineral | | TWA (Inhal- able fraction) | 5 mg/m3 | ACGIH |

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

| Engineering measures | : | The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. |
|----------------------|---|---|
| | | |

Where material is heated, sprayed or mist formed, there is

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version 2.0 | Revision Date: 08/31/2018 | SDS Number: 800010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|----------------|--|--|--|
| | | greater potentia | I for airborne concentrations to be generated. |
| | | controls. Educate and tra measures releva product. Ensure appropri equipment used equipment, loca Drain down syst nance. Retain drain dow subsequent recy Always observe washing hands a drinking, and/or protective equip taminated clothi | es for safe handling and maintenance of in workers in the hazards and control ant to normal activities associated with this ate selection, testing and maintenance of to control exposure, e.g. personal protective I exhaust ventilation. em prior to equipment break-in or mainte- which is sealed storage pending disposal or ycle. good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ng and footwear that cannot be cleaned. |
| Dorog | nal protoctivo oquipr | Practice good he | ousekeeping. |
| | nal protective equipr ratory protection | : No respiratory p conditions of use In accordance w tions should be If engineering co tions to a level w select respirator cific conditions of Check with resp Where air-filterin priate combinati Select a filter su | rotection is ordinarily required under normal e. vith good industrial hygiene practices, precau- taken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, y protection equipment suitable for the spe- of use and meeting relevant legislation. iratory protective equipment suppliers. ng respirators are suitable, select an appro- on of mask and filter. itable for the combination of organic gases ype A/Type P boiling point >65°C (149°F)]. |
| | protection marks | gloves approved US: F739) made suitable chemica gloves Suitability usage, e.g. frequ sistance of glove glove suppliers. Personal hygien Gloves must on gloves, hands sl | ntact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber y and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. ie is a key element of effective hand care. by be worn on clean hands. After using hould be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. |

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for >

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version 2.0 | Revision Date: 08/31/2018 | | | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|------------------|------------------------------|------|---|---|
| | | | short-term/splash p recognize that suita may not be availab time maybe accept and replacement re a good predictor of dependent on the e Glove thickness sh | suitable gloves can be identified. For protection we recommend the same, but able gloves offering this level of protection le and in this case a lower breakthrough able so long as appropriate maintenance egimes are followed. Glove thickness is not glove resistance to a chemical as it is exact composition of the glove material. ould be typically greater than 0.35 mm love make and model. |
| Eye p | rotection | : | Wear full face shiel | d if splashes are likely to occur. |
| Skin a | and body protection | : | Wear chemical resi risk of splashing, al | stant gloves/gauntlets and boots. Where so wear an apron. |
| Protec | ctive measures | : | | equipment (PPE) should meet recom- andards. Check with PPE suppliers. |
| Therm | nal hazards | : | Not applicable | |
| Envir | onmental exposure co | ntro | ls | |
| Gener | ral advice | : | vant environmental of the environment necessary, prevent charged to waste w municipal or indust discharge to surfac Local guidelines on | neasures to fulfill the requirements of rele- protection legislation. Avoid contamination by following advice given in Chapter 6. If undissolved material from being dis- vater. Waste water should be treated in a rial waste water treatment plant before e water. e mission limits for volatile substances for the discharge of exhaust air containing |
| SECTION | 9. PHYSICAL AND CHE | ΞΜΙΟ | CAL PROPERTIES | |
| Appea | arance | : | liquid | |
| Colou | r | : | Clear amber | |
| Odour | r | : | Slight hydrocarbor | 1 |
| Odour | r Threshold | : | Data not available | |
| pН | | : | Not applicable | |
| pour p | point | : | -45 °C / -49 °F Method: ASTM D5 | 950 |
| Initial range | boiling point and boiling | : | > 280 °C / 536 °F estimated value(s) | |
| Flash | point | : | 212 °C / 414 °F | |
| | | | 7 / 17 | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Vers 2.0 | | Revision Date: 08/31/2018 | | S Number: 0010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|-------------|------------------------|---------------------------------------|---|-----------------------------------|--|
| | | | | Method: ASTM D | 993 (PMCC) |
| | Evapora | tion rate | : | Data not availabl | e |
| | Flammal | bility (solid, gas) | : | Data not availabl | e |
| | Upper ex flammab | xplosion limit / upper ility limit | : | Typical 10 %(V) | |
| | Lower ex flammab | kplosion limit / Lower ility limit | : | Typical 1 %(V) | |
| | Vapour p | pressure | : | < 0.5 Pa (20 °C / | 68 °F) |
| | | | | estimated value(| S) |
| | Relative | vapour density | : | > 1 estimated value(s) | s) |
| | Relative | density | : | 0.863 (15 °C / 59 | °F) |
| | Density | | : | 863 kg/m3 (15.0 Method: ASTM D | |
| | Solubility Wate | /(ies) r solubility | : | negligible | |
| | Solub | pility in other solvents | : | Data not availabl | e |
| | Partition octanol/v | coefficient: n- water | : | log Pow: > 6 (based on inform | ation on similar products) |
| | Auto-ign | ition temperature | : | > 320 °C / 608 °F | : |
| | Decomp | osition temperature | : | Data not availabl | e |
| | Viscosity Visco | r sity, dynamic | : | Data not availabl | e |
| | Visco | sity, kinematic | : | 15.15 mm2/s (10 | 0 °C / 212 °F) |
| | | | | Method: ASTM D | 0445 |
| | Explosiv | e properties | : | Not classified | |
| | Oxidizin | g properties | : | Data not availabl | e |
| | Conduct | ivity | : | This material is n | ot expected to be a static accumulator. |

SECTION 10. STABILITY AND REACTIVITY

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version 2.0 | Revision Date: 08/31/2018 | | S Number: 0010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|----------------|---|---|-------------------------|--|
| Read | stivity | : | | s not pose any further reactivity hazards in listed in the following sub-paragraph. |
| Cher | Chemical stability | | Stable. | |
| | Possibility of hazardous reac- tions | | Reacts with stror | ng oxidising agents. |
| Cond | litions to avoid | : | Extremes of tem | perature and direct sunlight. |
| Incor | npatible materials | : | Strong oxidising | agents. |
| Haza prod | ardous decomposition | : | No decompositio | n if stored and applied as directed. |

SECTION 11. TOXICOLOGICAL INFORMATION

| Basis for assessment | : | Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |
|----------------------|---|---|
| | | , |

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

| Acute oral toxicity | : | LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met. |
|---------------------------|---|---|
| Acute inhalation toxicity | : | Remarks: Based on available data, the classification criteria are not met. |
| Acute dermal toxicity | : | LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met. |

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Shell Rotella T5 NG 15W-40

| Version | Revision Date: |
|---------|----------------|
| 2.0 | 08/31/2018 |

SDS Number: 800010025929

Print Date: 09/01/2018 Date of last issue: 02/09/2016

Respiratory or skin sensitisation

Product:

Remarks: Expected to be a skin sensitizer.

Components:

Calcium alkaryl sulphonate: Remarks: May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

| IARC | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. |
|-----------------------|---|
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. |
| ΝΤΡ | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |
| Reproductive toxicity | |
| Product: | |

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Shell Rotella T5 NG 15W-40

Version Revision Date: 2.0 08/31/2018

SDS Number: 800010025929

Print Date: 09/01/2018 Date of last issue: 02/09/2016

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

| Basis for assessment | : | Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract). |
|--|---|---|
| Ecotoxicity | | |
| Product: Toxicity to fish (Acute toxici- ty) | : | Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met. |
| Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) | : | Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met. |
| Toxicity to algae (Acute tox- icity) | : | Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version 2.0 | Revision Date: 08/31/2018 | | 0S Number: 0010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|----------------|--|-----|---|--|
| | | | Based on availabl | e data, the classification criteria are not met. |
| To icit | xicity to fish (Chronic tox- y) | : | Remarks: Data no | ot available |
| aq | xicity to daphnia and other uatic invertebrates (Chron- oxicity) | : | Remarks: Data no | ot available |
| | xicity to microorganisms cute toxicity) | : | Remarks: Data no | ot available |
| Co | mponents: | | | |
| All | cylphenol: | | | |
| M- icit | Factor (Acute aquatic tox- y) | : | 1 | |
| Ре | rsistence and degradabili | ity | | |
| | <u>oduct:</u> odegradability | : | Major constituents | dily biodegradable. s are inherently biodegradable, but contains may persist in the environment. |
| Bie | paccumulative potential | | | |
| | oduct: baccumulation | : | Remarks: Contair cumulate. | is components with the potential to bioac- |
| Мс | bility in soil | | | |
| Pr | oduct: | | | |
| | bility | : | | under most environmental conditions. vill adsorb to soil particles and will not be |
| | | | Remarks: Floats o | on water. |
| Ot | her adverse effects | | | |
| <u>Pr</u> | oduct: | | | |
| | ditional ecological infor- tion | : | ozone creation po Product is a mixtu | one depletion potential, photochemical tential or global warming potential. Ire of non-volatile components, which will not in any significant quantities under normal |
| | | | Poorly soluble mix Causes physical f | cture. ouling of aquatic organisms. |

Shell Rotella T5 NG 15W-40

| Version | Revision Date: | SDS Number: | Print Date: 09/01/2018 |
|---------|----------------|--------------|--------------------------------|
| 2.0 | 08/31/2018 | 800010025929 | Date of last issue: 02/09/2016 |

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13. DISPOSAL CONSIDERATIONS

| Disposal methods | | |
|------------------------------|---|---|
| Waste from residues | : | Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses |
| | | Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. |
| Contaminated packaging | : | Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations. |
| Local legislation Remarks | : | Disposal should be in accordance with applicable regional, national, and local laws and regulations. |

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or

Shell Rotella T5 NG 15W-40

| Version | Revision Date: | SDS Number: | Print Date: 09/01/2018 |
|---------|----------------|--------------|--------------------------------|
| 2.0 | 08/31/2018 | 800010025929 | Date of last issue: 02/09/2016 |

needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

| SARA 311/312 Hazards | : | Respiratory or skin sensitisation |
|----------------------|---|---|
| SARA 313 | : | This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. |

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

| Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), hydrotreated light paraffinic lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based | 64742-65-0 64742-54-7 64742-55-8 72623-86-0 |
|---|--|
| Zinc dialkyldithiophosphate | 68649-42-3 |
| Distillates (petroleum), hydrotreated light | 64742-47-8 |

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

California List of Hazardous Substances

| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 |
|---|------------|
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 |
| Distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 |
| lubricating oils (petroleum), C15-30, hydrotreated neutral oil- | 72623-86-0 |
| based | |

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version 2.0 | Revision Date: 08/31/2018 | | OS Number: 0010025929 | Print Date: 09/01/2018 Date of last issue: 02/09/2016 |
|----------------|------------------------------|-------------|--------------------------|--|
| The c | • | produc : | • | in the following inventories: s listed or polymer exempt. |
| TSCA | A | : | All components | s listed. |
| DSL | | : | All components | s listed. |

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 1, 1, 0 tivity)

Full text of other abbreviations

| ACGIH OSHA Z-1 ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms | : | USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants 8-hour, time-weighted average 8-hour time weighted average The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites. |
|--|---|---|
| | | ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Chemicals Agency EINECS = The European Inventory of Existing Commercial Chemical Substances EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substances Inventory EWC = European Waste Code |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T5 NG 15W-40

| Version | Revision Date: | SDS Number: | Print Date: 09/01/2018 |
|---------|----------------|---|---|
| 2.0 | 08/31/2018 | 800010025929 | Date of last issue: 02/09/2016 |
| | | Labelling of Ch IARC = Internat IATA = Internat IC50 = Inhibitor IL50 = Inhibitor IMDG = Internat INV = Chinese IP346 = Institu determination of KECI = Korea B LC50 = Lethal I LL/EL/IL = Leth LL50 = Lethal I LL/EL/IL = Leth LL50 = Lethal I MARPOL = Inter Pollution From NOEC/NOEL = served Effect L OE_HPV = Occ PBT = Persiste PICCS = Philip Substances PNEC = Predic REACH = Regi Chemicals RID = Regulatin gerous Goods I SKIN_DES = S STEL = Short to TRA = Targeter TSCA = US To TWA = Time-W | tional Agency for Research on Cancer ional Air Transport Association by Concentration fifty y Level fifty ational Maritime Dangerous Goods Chemicals Inventory te of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. Ial Loading/Effective Loading/Inhibitory loading Loading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume nt, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical ted No Effect Concentration stration Evaluation And Authorisation Of ons Relating to International Carriage of Dan- |

Due to a change in detail in Section 15, this document has been released as a significant change. A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not

SAFETY DATA SHEET According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Shell Rotella T5 NG 15W-40

| Version | Revision Date: 08/31/2018 | SDS Number: | Print Date: 09/01/2018 |
|---------|---------------------------|--------------|--------------------------------|
| 2.0 | | 800010025929 | Date of last issue: 02/09/2016 |
| | | | |

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN